

TENSION METER WF-TC 1.0



Benefits at a glance:

- Ergonomic shape for optimal one-hand operation
- Small sensor head on flexible gooseneck for measurements also on heavy accessible places
- Modern, especially high-contrast OLED Display for good readability also from different angles
- Integrated, sustainable lithium polymer battery includes USB-C charging cable
- Compact in set including europlug and hardcase

Technische Daten

Measuring range	10 – 600 Hz
Accuracy	10 – 400 Hz: ± 1% 400 – 600 Hz: ± 2%
Resolution	10 – 99,9 Hz: 0,1 Hz > 100 Hz: 1 Hz
Measuring Method	contactless acoustic
Power supply	Integrated, sustainable lithium polymer battery 3,7 V / 850 mAh
Operational hours	ca. 16 h continuous measurement
Power consumption	< 50 mA
Display	OLED-Display, monochrom weiß, Punkt Matrix 128 x 64 Pixel, Displaygröße 37 x 19,5 mm
Sensor	acoustic sensor with background fade out on flexible gooseneck approx. 165 mm total length
Dimensions (without gooseneck)	approx. 130 x 60 x 30 mm
Mass	approx. 125 g

CUSTOMER-SPECIFIC SOLUTIONS

Do you need additional features such as data transfer via Bluetooth to your system? Just contact us! We would be glad to coordinate with you an individual execution of the WF-TC measuring instrument from.



leandrive@walther-flender.de



Telefon: +49 211 7007 107