

WALTHER FLENDER TRANSPORT TIMING BELTS - MINIMUM NUMBERS OF TEETH FOR CAMS / PROFILES

Minimum number of teeth for profiles/cams above tooth

Profilfußbreite (mm)	2	3	5	6	8	10	11	13	16	19
HYBRID 8M	20	20	20	24	30	40	50	60	100	
T5	12	12	18	25	40	50	60	100		
AT5 / ATL5	15	15	18	25	40	50	60	100		
T10 / T10-HF	14	14	16	16	18	25	35	45	80	100
AT10	15	15	18	18	22	25	35	45	80	100
ATL10 / ATL10-HF	25	25	25	25	25	25	35	45	80	100
T20 / AT20	18	18	18	18	18	18	18	20	35	50
ATL20	30	30	30	30	30	30	30	30	35	50
HTD® 5M	14	14	16	25	40	50	60	100		
HTD® 8M	20	20	20	24	30	40	50	60	100	
HTD® 14M	28	28	28	28	28	28	30	30	50	72

Minimum number of teeth for profiles/cams over tooth space

Profilfußbreite (mm)	2	3	5	6	8	10	11	13	16	19
HYBRID 8M	20	20	40	45	55	60	70	80	100	
T5	12	30	45	50	60	100				
AT5 / ATL5	15	30	45	50	60	100				
T10 / T10-HF	18	20	30	40	45	50	55	65	80	100
AT10	18	20	30	40	45	50	55	65	80	100
ATL10 / ATL10-HF	25	25	30	40	45	50	55	65	80	100
T20 / AT20	18	18	20	30	40	45	50	54	58	60
ATL20	30	30	30	30	40	45	50	54	58	60
HTD® 5	18	30	45	50	60	100				
HTD® 8	20	20	40	45	55	60	70	80	100	
HTD® 14	28	28	30	42	58	64	72	78	82	86
HTD® L14	43	43	43	43	58	64	72	78	82	86